

[Home](#) ▶ [Equipment](#) ▶ [Loaders](#) ▶ [Compact Wheel Loaders](#) ▶ L65

L65

Compact Wheel Loader



- Bobcat Tier 4, turbo-charged engine delivers powerful, high-torque performance, high efficiency and convenient service
- Articulated steering for a tight-turning radius and high maneuverability
- High bucket capacity (7/8 cubic yard) and 10.5-foot lift height
- Full-color, 5-inch display panel
- Seat-mounted joystick

Get financing as low as 0% for 24 months* or a \$1,500 USD*/\$2,000 CAD* rebate in lieu of financing on the L65 compact wheel loader.

[Build & Quote](#)

[Contact Dealer](#)

[View Offers](#)

[Find Dealer](#)[Download Brochure](#)

L65 Overview

With a high bucket capacity, high lift height, impressive maneuverability and swift travel speeds it's hard to beat the material-handling capabilities of the Bobcat® L65 compact wheel loader. This durable compact wheel loader delivers the performance, versatility and premium comfort to power through tough jobs in tight spaces.

L65 Specs & Compare

L65 Key Specifications

Horsepower	55 hp
Rated Operating Capacity with Bucket (Straight)	3,133 lb
Rated Operating Capacity with Bucket (Articulated)	2,618 lb
Rated Operating Capacity with Forks (Straight)	3,759 lb
Rated Operating Capacity with Forks (Articulated)	3,172 lb
Bucket Capacities	0.86- 1.3 yd ³
Operating Weight	9944 lb
Auxiliary Std Flow	19.8 gal/min
Pump Capacity	19.8 gal/min
Width (over tires)	69.7 in

Engine

Emissions Tier (EPA)	Tier 4
Engine Cooling	Liquid
Engine Fuel	Diesel
Horsepower	55 hp
Turbocharged Engine	yes

Performance

Rated Operating Capacity with Bucket (Straight)	3,133 lb
---	----------

Rated Operating Capacity with Bucket (Articulated)	2,618 lb
Rated Operating Capacity with Forks (Straight)	3,759 lb
Rated Operating Capacity with Forks (Articulated)	3,172 lb
Tipping Capacity with Bucket (Straight)	6,266 lb
Tipping Capacity with Bucket (Articulated)	5,236 lb
Bucket Capacities	0.86- 1.3 yd ³
Operating Weight	9944 lb

Capacities

Fuel Tank	20.8 gal
-----------	----------

Hydraulic System

Auxiliary Std Flow	19.8 gal/min
Pump Capacity	19.8 gal/min

Drive System

Drive Type	2-speed hydrostatic with Advanced Attachment Control
------------	--

Dimension

Length with Standard Bucket	218 in
Width (over tires)	69.7 in
Width (with bucket)	74.8 in
Inside Turning Radius w Bucket	2000 mm
Turning Radius Outside	169.2 in
Outside Turning Radius w Forks	4591 mm
Wheelbase	82.7 in
Articulation Angle	40°
Oscillation Angle	8°
Dump Angle @ Maximum Height	45°
Ground Clearance	11.3 in
Height to Bucket Hinge Pin	10.58 ft
Rollback Angle	55°
Tire Size	365/70 R18

Wheel Tread	55.5 in
Height with Operator Cab	97.3 in

Features

Operator Canopy	Optional
Enclosed Operator Cab w HVAC	Standard
Mechanical Susp Seat	Standard
Air Ride Susp Seat	Not Applicable
Joystick Control	Standard
Keyed Ignition	Optional
Keyless Ignition	Standard
Speedometer	Standard
Hour Meter	Standard
Tilt and Telescoping Steering Wheel	Standard
Travel Foot Pedal	Standard
Cup Holders	Standard
Front and Rear Work Lights	Standard
Road Lights	Standard
Rotating Flashing Beacon	Optional
Four Way Flasher	Standard
Turn Signals	Standard
Advanced Attachment Control	Standard
Auxiliary Hydraulics	Standard
Engine Derate	Standard
Glow Plug Engine Preheat	Standard
High Flow	Not Applicable
Hydrostatic Transmission	Standard
Tilt Lock Out	Standard
Two Speed Travel	Standard
Z Bar Linkage	Standard
Backup Alarm	Standard

Horn	Standard
Lift Arm Lockout with Manual Bypass	Standard
Lift-Arm Support	Standard
OICS System	Standard
Rear View Camera	Optional
Seat Switch	Standard
Side Mirrors Right and Left	Standard
Wheel Fenders	Standard